

# TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing



## **RF Connectors Technical Data Sheet**

PE4470

## Configuration

- TNC Male Connector
- MIL-C-39012
- •50 Ohms
- Straight Body Geometry

#### **Features**

Solder Cup Interface Type

Solder Attachment

4 Hole Flange

Gold Plated Brass Contact

3 µin minimum contact plating

## **Applications**

General Purpose Test

Rack and Panel Mount Applications

#### **Description**

Pasternack's PE4470 TNC male connector solder attachment 4 hole flange mount solder cup terminal, .531 inch hole spacing is part of our full line of RF components available for same-day shipping. This TNC 4 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount

Our TNC male 4 hole flange connector PE4470 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

#### **Mechanical Specifications**

#### Size

Length 1.214 in [30.84 mm] Width/Dia. 0.75 in [19.05 mm] 0.75 in [19.05 mm] Height Weight 0.05 lbs [22.68 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing PE4470





# TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing



### **RF Connectors Technical Data Sheet**

PE4470

#### **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold 3 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 70 µin minimum
Coupling Nut	Brass	Nickel 70 μin minimum

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing PE4470

URL: https://www.pasternack.com/tnc-male-standard-solder-cup-terminal-connector-pe4470-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



© 2016 Pasternack Enterprises All Rights Reserved

# PE4470 CAD Drawing

TNC Male Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .531 inch Hole Spacing

