



MMCX Jack Connector Crimp/Solder Attachment For RG316-DS, RG188-DS

TECHNICAL DATA SHEET

PE44852

MMCX Jack Connector Crimp/Solder Attachment For RG316-DS, RG188-DS

Configuration

Connector MMCX Jack

Connector Interface Type RG316-DS,RG188-DS

Cable Attachment Method (Shield/Contact)

Crimp/Solder
Body Style

Straight

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Size

 Length, in [mm]
 1 [25.4]

 Width/Dia., in [mm]
 0.157 [3.99]

 Weight, lbs [g]
 0.004 [1.81]

Connector

Type MMCX Jack

Contact Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Gold Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data

Notes: Values at 25 °C, sea level

MMCX Jack Connector Crimp/Solder Attachment For RG316-DS, RG188-DS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: MMCX Jack Connector Crimp/Solder Attachment For RG316-DS, RG188-DS PE44852

URL: http://www.pasternack.com/mmcx-jack-standard-rg316-ds-rg188-ds-connector-pe44852-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



