

N Male Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .640 inch DD Hole



RF Connectors Technical Data Sheet

PE4489

Configuration

- N Male Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry

Features

- Max. Operating Frequency 6 GHz
- Good VSWR of 1.3:1

Applications

General Purpose Test

- Solder Cup Interface Type
- Solder Attachment
- Bulkhead
- Gold Plated Brass Contact
- 30 µin minimum contact plating
- Rack and Panel Mount Applications

Description

Pasternack's PE4489 type N male bulkhead mount connector solder attachment solder cup terminal, .640 inch DD hole is part of our full line of RF components available for same-day shipping. Our type N male connector operates up to a maximum frequency of 6 GHz and offers good VSWR of 1.3:1. This type N bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our type N male bulkhead connector PE4489 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

Electrical Specifications

Minimum	Typical	Maximum	Units
DC		6	GHz
		1.3:1	
		1,000	Vrms
			DC 6 1.3:1

Mechanical Specifications

Size	
Length	1.59 in [40.39 mm]
Width/Dia.	0.787 in [19.99 mm]
Weight	0.102 lbs [46.27 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .640 inch DD Hole PE4489

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com







Solder Cup Terminal, .640 inch DD Hole

N Male Bulkhead Mount Connector Solder Attachment

PE4489

RF Connectors Technical Data Sheet

Matorial Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum
Coupling Nut	Brass	Nickel 100 µin minimum

Environmental Specifications

Temperature Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

N Male Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .640 inch DD Hole from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .640 inch DD Hole PE4489

URL: https://www.pasternack.com/n-male-standard-solder-cup-terminal-connector-pe4489-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com



PE4489 CAD Drawing N Male Bulkhead Mount Connector Solder Attachment

Solder Cup Terminal, .640 inch DD Hole

