



SMP Male Full Detent Shroud Thread-In Mount

TECHNICAL DATA SHEET

PE44906

Configuration

Connector SMP Male, Full Detent

Connector Specification MIL-STD-348

Connector Interface Type None
Attachment Method (Shield/Contact) None
Body Style Straight

Body Style Straight
Mount Method Thread-In

Electrical Specifications

Impedance 50 Ohms

Mechanical Specifications

Size

 Length
 0.16 in [4.06 mm]

 Width/Dia.
 0.12 in [3.05 mm]

 Weight
 0.082 lbs [37.19 g]

Connector

Type SMP Male

Body Material and Plating Passivated Stainless Steel

Body Plating Specification QQ-P-35

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Plotted and Other Data

Notes:

• Values at +25 °C, sea level

SMP Male Full Detent Shroud Thread-In Mount from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Shroud Thread-In Mount PE44906

URL: http://www.pasternack.com/smp-male-standard-shroud-pe44906-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE44906 CAD Drawing SMP Male Full Detent Shroud Thread-In Mount

