

## SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel



#### RF Connectors Technical Data Sheet

PE4529

#### Configuration

- SMA Female Connector
- MIL-STD-348
- •50 Ohms
- Straight Body Geometry

#### **Features**

Gold Plated Contact

- Solder Cup Interface Type
- Solder Attachment
- Bulkhead

Contact plating according to MIL-G-45204

#### **Applications**

General Purpose Test

Rack and Panel Mount Applications

#### **Description**

Pasternack's PE4529 SMA female bulkhead mount connector solder attachment solder cup terminal, .235 inch D hole is part of our full line of RF components available for same-day shipping. This SMA bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount

Our SMA female bulkhead connector PE4529 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

#### **Mechanical Specifications**

#### Size

Length 0.668 in [16.97 mm] Width/Dia. 0.437 in [11.10 mm] Weight 0.008 lbs [3.63 g]

#### **Material Specifications**

Description		Material	Plating
Contact			Gold MIL-G-45204
Insulation		PTFE	
Body		Stainless Steel	Gold MIL-G-45204

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel PE4529





# SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel



### **RF Connectors Technical Data Sheet**

PE4529

Environmental Specifications Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

**Plotted and Other Data** 

Notes:

SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel PE4529

URL: https://www.pasternack.com/sma-female-standard-solder-cup-terminal-connector-pe4529-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



© 2016 Pasternack Enterprises All Rights Reserved

# PE4529 CAD Drawing

SMA Female Bulkhead Mount Connector Solder Attachment Solder Cup Terminal, .235 inch D Hole, .093 inch Max Panel

