

75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing



RF Connectors Technical Data Sheet

PE4630

Configuration

- BNC Female Connector
- 75 Ohms
- Straight Body Geometry

- Solder Cup Interface Type
- Solder Attachment
- 4 Hole Flange

Features

Gold Plated Brass Contact

Applications

• General Purpose Test

Rack and Panel Mount Applications

Description

Pasternack's PE4630 75 ohm BNC female connector solder attachment 4 hole flange mount solder cup terminal, .500 inch hole spacing is part of our full line of RF components available for same-day shipping. This BNC 4 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our 75 ohm BNC female 4 hole flange connector PE4630 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable connector assemblies for you and ship same-day.

Mechanical Specifications

Size

 Length
 1.057 in [26.85 mm]

 Width/Dia.
 0.687 in [17.45 mm]

 Height
 0.687 in [17.45 mm]

 Weight
 0.027 lbs [12.25 g]

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Nickel

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing PE4630

ISO 9001 : 2008 Registered



75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing



RF Connectors Technical Data Sheet

PE4630

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing PE4630

URL: https://www.pasternack.com/bnc-female-standard-solder-cup-terminal-connector-pe4630-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE4630 CAD Drawing

75 Ohm BNC Female Connector Solder Attachment 4 Hole Flange Mount Solder Cup Terminal, .500 inch Hole Spacing

