



Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm, 2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs

Torque Wrenches Technical Data Sheet

PE5019-1A

Features

- Break-over design prevents over-torquing
- Blue anodized aluminum handle
- Each break-over torque wrench comes secured inside a labeled wooden box

Applications

- Lab environments
- Production cable attachment
- Field install and testing
- Applying accurate torque
- Preventing over torque

Description

Pasternack's PE5019-XX break-over torque wrenches allow accurate mating force when assembling and disassembling a variety of RF coaxial connectors. The unique feature of break-over torque wrenches is that they will "break" at the pivot point once the preset torque value force is achieved, effectively preventing the user from over tightening the coupling nut on the connector. Our break-over torque wrenches are lab-quality tools made with a durable nickel-plated steel alloy wrench head connected to a light weight, blue anodized aluminum handle. These RF torque wrenches are secured inside a latched and labeled wooden box for proper storage.

Configuration

Torque Type	Fixed
Design Type	Break-Over
Hex Size	5/16 inch
Torque Setting	8 in-lbs [0.9 Nm]
Torque Accuracy	±0.32 in-lbs [±0.04 Nm]
Weight	0.543 lbs [246.3 g]
Handle Color	Blue
Wrench Head Material	Steel
Wrench Head Plating	Nickel
Handle Material	Blue Anodized Aluminum

Compliance Certifications (see [product page](#) for current document)

Notes:

Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm, 2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm, 2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs PE5019-1A](#)



Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm,
2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs

Torque Wrenches Technical Data Sheet

PE5019-1A


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm, 2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs PE5019-1A](https://www.pasternack.com/break-over-wrench-5-16-bit-3.5mm2.92mm-2.4mm-sma-8in-lbs-pe5019-1a-p.aspx)

URL: <https://www.pasternack.com/break-over-wrench-5-16-bit-3.5mm2.92mm-2.4mm-sma-8in-lbs-pe5019-1a-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE5019-1A CAD Drawing

Fixed Break-Over Torque Wrench With 5/16 Bit For 3.5mm,
2.92mm, 2.4mm, SMA Connectors Pre-set to 8 in-lbs



STANDARD TOLERANCES

.X	±0.2
.XX	±0.1
.XXX	±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE

PE5019-1A

CAGE CODE

53919

CAD FILE

050217

SCALE

N/A

SIZE

A

2233

PE

PASTERNAK

THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com