

Irvine, CA 92623-6759

Toll Free: (866) 727-8376 Direct: +1 (949) 261-1920 FAX: +1 (949) 261-7451 Sales: sales@pasternack.com

Tech Support: techsupport@pasternack.com

PE51006 Wideband Mobile Antenna, 406 - 512 MHz, 2 dB

Product Features

- 106 MHz bandwidth
- No tuning required
- NMO Mount base

Description

The PE51006 antenna offers excellent bandwidth and low VSWR across the 406 to 512 MHz UHF band. The base and matching coil design is able to withstand high shock environments. The antenna mates with the popular NMO mount design. See the Pasternack catalog or website for the widest selection of NMO cable configurations.

Electrical Specifications (1)

=:001:104:0 001:101:10		
Parameter	Units	Value
Impedance	Ohms	50
Frequency	MHz	406 - 512
VSWR across bandwidth		< 2.0:1
Gain, ground plane	dB	2.0
Gain, no ground plane	dB	0
Power Rating	Watts	150

Mechanical Specifications (1)

Parameter	Value
Antenna Height	Approximately 12"
Whip Diameter	0.10"
Weight	0.6 lbs.
Whip Material	Stainless Steal
Base Coil Housing	Molded polymer jacket & nickel and chrome
	plated brass bushing
Mating Mount	NMO



Ordering Information

Part Number	Description
PE51006	Wideband Mobile Antenna, 106 MHz BW @ 2:1 VSWR, No GP required