



2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna

Antennas Technical Data Sheet

PE51OM1007

Features

- True 360 degree omni directional antennas which feature patent pending technology
- Dual polarity/dual frequency feed system in single enclosure
- MIMO - Multiple-Input and Multiple-Output, separate inputs for 2.4 GHz and 5 GHz - four connectors total
- UV-Resistant radome for all-weather operation
- Heavy duty industrial grade design

Applications

- 2.4/5 GHz IEEE 802.11a/b/g and 802.11ac applications
- Supports 1x2, 2x2 and 4x4 MIMO AP/Routers
- WiMax, WISP and WiFi applications
- Wireless video systems
- Point-to-multipoint applications

Description

The HyperGain PE51OM1007 is a professional high gain dual band/dual polarity omnidirectional base station antenna designed and optimized for 2.4 and 5 GHz frequencies. This antenna is ideally suited for multipoint applications where long range and wide coverage is desired. The DPU series stands out from the competition since they are true 360 degree omni directional antennas which feature patent pending technology.

The PE51OM1007 is actually four antennas in one, a 2.4 GHz dual polarized antenna and a 5 GHz dual polarized antenna together in a single radome. Each frequency features separate feeds for both horizontal and vertical polarities, four N-Female connectors total. This antenna incorporates advanced dual polarization technology that allows for the interoperability of two radio transmit and receive paths. This technology allows for the attenuation of unwanted signals from adjacent channels and/or co-located equipment.

The PE51OM1007 construction features a heavy-duty UV resistant PVC radome for durability and aesthetics. Designed to operate in the harshest of environments, the PE51OM1007 far exceeds other omnidirectional antennas. The included mounting system features twin heavy-duty mounting clamps and bolts for superior strength.

Configuration

Design	Omni
Band Type	Dual
Radiation Pattern	Omni Directional
Polarization	Vertical/Horizontal
Connector Type	N Female
Interface 2	N Female
Interface 3	N Female
Interface 4	N Female
Number of Ports	4
Lightning Protection	DC Ground

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Input VSWR			1.6:1	
Impedance		50		Ohms
Gain		6		dBi
Isolation	28			dB
Input Power			100	Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE51OM1007](#)



2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna

Antennas Technical Data Sheet

PE510M1007

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	2,400-2,500	5,100-5,800				MHz
Gain	6	9				dBi
Horizontal Beam Width	360	360				Degees
Vertical Beam Width	28	14				Degees
VSWR Max 1.6:1	1.8:1					
Maximum Input Power	100	100				Watts

Mechanical Specifications

Radome Material	PVC
Size	
Radome Diameter	2.9 in [73.66 mm]
Overall Length	38.3 in [972.82 mm]
Width	2.9 in [73.66 mm]
Height	2.9 in [73.66 mm]
Mounting Mast Diameter	1.6 to 3.5 in [40.64 to 88.90 mm]
Weight	6.5 lbs [2.95 kg]
Mechanical Specification Notes:	
Radome material is UV resistant PVC.	

Environmental Specifications

Temperature	
Operating Range	-40 to +60 deg C
Wind Loading	130 MPH [209.21 KPH]

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE510M1007](#)



2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna


Antennas Technical Data Sheet

PE510M1007


Typical Radiation Pattern

RF Antenna Patterns


Horizontal Polarization




H-Plane: 2400 MHz




V-Plane: 2400 MHz




H-Plane: 2450 MHz



V-Plane: 2450 MHz



H-Plane: 2500 MHz



V-Plane: 2500 MHz

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE510M1007](#)




2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna


Antennas Technical Data Sheet

PE51OM1007


Horizontal Polarization




H-Plane: 5100 MHz




V-Plane: 5100 MHz




H-Plane: 5500 MHz



V-Plane: 5500 MHz



H-Plane: 5800 MHz



V-Plane: 5800 MHz

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE51OM1007](#)




2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna


Antennas Technical Data Sheet

PE510M1007


Vertical Polarization




H-Plane: 2400 MHz




V-Plane: 2400 MHz




H-Plane: 2450 MHz



V-Plane: 2450 MHz



H-Plane: 2500 MHz



V-Plane: 2500 MHz

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE510M1007](#)




2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna


Antennas Technical Data Sheet

PE510M1007


Vertical Polarization




H-Plane: 5100 MHz




V-Plane: 5100 MHz




H-Plane: 5500 MHz



V-Plane: 5500 MHz



H-Plane: 5800 MHz



V-Plane: 5800 MHz

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE510M1007](#)



2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna

Antennas Technical Data Sheet

PE51OM1007

2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna PE51OM1007](https://www.pasternack.com/dual-antenna-6-dbi-gain-n-pe51om1007-p.aspx)

URL: <https://www.pasternack.com/dual-antenna-6-dbi-gain-n-pe51om1007-p.aspx>





The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE51OM1007 CAD Drawing

2.4/ 5 GHz 9 dBi Dual Band / Dual Polarized Omni Antenna

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	2/13/2020	M.MILLER



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5.08] FRACTIONS ± 1/32
.XX = ±.02 [.51] ANGLES ± 1°
.XXX = ±.005 [.13]

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5% / L -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

PE PASTERNAK
an INFINIT brand

Pasternack Enterprises, Inc.
P. O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE: A CAGE CODE: A DRAWN BY: K.DANG ITEM NO: PE51OM1007

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION. ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE: N/A

REV: A

REGULATORY COMPLIANCE:
EU RoHS DIRECTIVE (MOST RECENT RELEASED VERSION)

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.