



0.5 Watt RF Load Up to 12.4 GHz With SMA Male Input Passivated Stainless Steel

RF Terminations Technical Data Sheet

PE6002

Features

- DC to 12.4 GHz Frequency Range
- VSWR 1.17:1 Max
- Max Power 0.5 Watt (CW)
- SMA Male Coaxial Interface

Applications

- Wireless
- Radar Systems
- Commercial and Military Communication
- SatCom
- Test and Measurement

Description

Pasternack's PE6002 is an RF termination (also called RF load or dummy load) that operates from DC to 12.4 GHz and handles up to 0.5 Watt (CW). Our SMA termination / load has a male gender. PE6002 SMA load termination offers 1.17:1 max VSWR.

RF load / terminations are indispensable components in many RF, microwave and millimeter wave systems where signal reflection from unused ports can potentially damage the device or reduce the signal integrity. By using a terminator on an unused port with a matched load (dummy load), the incident energy will be absorbed with minimal reflection. These termination components are commonly used to terminate devices such as couplers, circulators, and switches. They are also widely used in measurement systems to ensure accurate results. Pasternack offers a huge selection of RF, microwave and millimeter wave terminations up to 65 GHz with excellent performance over the entire operating range and power handling capabilities up to 800 Watt (CW).

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Impedance		50		Ohms
VSWR			1.17:1	
Input Power (CW)			0.5	Watts

Mechanical Specifications

Size	
Length	0.35 in [8.89 mm]
Width	0.315 in [8 mm]
Weight	0.004 lbs [1.81 g]
Configuration	
Connector	SMA Male
Connector Specification	MIL-STD-348
Hex Size	5/16 inch
Mating Torque	8 in-lbs [0.90 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0.5 Watt RF Load Up to 12.4 GHz With SMA Male Input Passivated Stainless Steel PE6002](#)



0.5 Watt RF Load Up to 12.4 GHz With SMA
Male Input Passivated Stainless Steel

RF Terminations Technical Data Sheet

PE6002

Material Specifications

Description	Material	Plating
Connector 1 Contact	Brass	Gold
Insulation	PTFE	
Body	Passivated Stainless Steel	
Coupling Nut	Passivated Stainless Steel	
Housing	Passivated Stainless Steel	

Environmental Specifications

Temperature

Operating Range -55 to +125 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

REACH Compliant 12/17/2015

Plotted and Other Data

Notes:

0.5 Watt RF Load Up to 12.4 GHz With SMA Male Input Passivated Stainless Steel from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [0.5 Watt RF Load Up to 12.4 GHz With SMA Male Input Passivated Stainless Steel PE6002](http://www.pasternack.com/0.5-watts-sma-male-rf-load-up-to-12.4-ghz-precision-pe6002-p.aspx)

URL: <http://www.pasternack.com/0.5-watts-sma-male-rf-load-up-to-12.4-ghz-precision-pe6002-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE6002 CAD Drawing

0.5 Watt RF Load Up to 12.4 GHz With SMA Male Input Passivated Stainless Steel



STANDARD TOLERANCES
DECIMAL
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES

PE PASTERNAK®
THE ENGINEER'S RF SOURCE
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE
PE6002

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

FSCM NO. 53919

CAD FILE 053116

SCALE N/A

SIZE A

3045