



50 Ohm 1 Watts Precision Passivated Stainless Steel
SMA Female RF Load With Chain Up To 26.5 GHz

TECHNICAL DATA SHEET

PE6080

50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 26.5 GHz

Configuration

RF Load Design	Precision
Connector	SMA Female
Connector Specification	MIL-STD-348
Heat Sink	Passivated Stainless Steel

Electrical Specifications

Frequency Range, GHz	DC to 26.5
Impedance, Ohms	50
Maximum VSWR	1.35:1
Maximum Input Power, Watts	1

Frequency 1

Frequency, GHz	DC to 18
VSWR	1.25:1

Frequency 2

Frequency, GHz	18 to 26.5
VSWR	1.35:1

Mechanical Specifications

Size

Length, in [mm]	0.6 [15.24]
Width/Dia., in [mm]	0.25 [6.35]

Connector

Type	SMA Female
Body Material and Plating	Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 26.5 GHz PE6080](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



50 Ohm 1 Watts Precision Passivated Stainless Steel
SMA Female RF Load With Chain Up To 26.5 GHz

TECHNICAL DATA SHEET

PE6080

Plotted and Other Data

Notes:

Values at 25 °C, sea level

50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 26.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [50 Ohm 1 Watts Precision Passivated Stainless Steel SMA Female RF Load With Chain Up To 26.5 GHz PE6080](http://www.pasternack.com/1-watts-sma-female-rf-load-up-to-26.5-ghz-precision-pe6080-p.aspx)

URL: <http://www.pasternack.com/1-watts-sma-female-rf-load-up-to-26.5-ghz-precision-pe6080-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE6080 CAD Drawing

50 Ohm 1 Watts Precision Passivated Stainless Steel SMA
Female RF Load With Chain Up To 26.5 GHz



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE	PE6080		
	FSCM NO.	53919	

**PASTERNAK®**
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAD FILE	072806	SCALE	N/A	SIZE	A	127
----------	--------	-------	-----	------	---	-----