



# 0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz

#### TECHNICAL DATA SHEET

PE7036-3

0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz

Configuration

Design Step, Bidirectional Attenuator

Connector 1 BNC Female
Connector 2 BNC Female
Body Material and Plating Aluminum

**Electrical Specifications** 

Frequency Range, MHz
Impedance, Ohms
Attenuation Value, dB
Step Size, dB
Step Type

DC to 1,000
50
102
11
Toggle

Maximum Input Power, Watts1Maximum Insertion Loss, dB1.2Maximum VSWR1.4:1

Frequency 1

 Range, MHz
 DC to 500

 VSWR
 1.2:1

 Attenuation Accuracy, dB
 ± 1

Frequency 2

 Range, MHz
 500 to 1,000

 VSWR
 1.4:1

 Attenuation Accuracy, dB
 ± 1.5

**Mechanical Specifications** 

Size

 Length, in [mm]
 7.67 [194.82]

 Width, in [mm]
 1.062 [26.97]

 Height, in [mm]
 1.062 [26.97]

Connector 1

Type BNC Female

Connector 2

Type BNC Female

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz PE7036-3

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





# 0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz

#### TECHNICAL DATA SHEET

PE7036-3

Compliance Certifications (visit www.Pasternack.com for current document)

**Plotted and Other Data** 

Notes:

Values at 25 °C, sea level

0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz PE7036-3

URL: http://www.pasternack.com/102db-step-bnc-female-bnc-female-1-watt-attenuator-pe7036-3-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



### PE7036-3 CAD Drawing

0 to 102 dB Toggle Step Attenuator, BNC Female To BNC Female With 1 dB Step Rated To 1 Watt Up To 1 GHz

