

20 dB Fixed Attenuator, 7/16 DIN Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz



TECHNICAL DATA SHEET

PE7204-20

Pasternack Enterprises line of 100W Attenuators N, SMA and TNC in-series and between-series c Passivated Stainless Steel SMA, TNC and N co 100W Attenuators come in 3 dB, 6 dB, 10 dB, 2	nectors are available
Configuration	
Design	Fixed, Directional Attenuator
Connector 1	7/16 DIN Female
Connector 2	7/16 DIN Female
Body Material and Plating	Aluminum Heatsink, Black Anodized
Electrical Specifications	
Frequency Range, GHz	DC to 6
Impedance, Ohms	50
Attenuation Value, dB	20
Maximum Input Power, Watts	100
Maximum VSWR	1.45:1
Frequency 1	
Range, GHz	DC to 2
VSWR	1.2:1
Attenuation Accuracy, dB	±1
Frequency 2	
Range, GHz	2 to 4
VSWR	1.35:1
Attenuation Accuracy, dB	±1
Frequency 3	
Range, GHz	4 to 6
VSWR	1.45:1
Attenuation Accuracy, dB	± 1.25
Mechanical Specifications	
Temperature	
Operating Range, deg C	-55 to +125

inventory and certifications: 20 dB Fixed Attenuator, 7/16 DIN Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz PE7204-20 information contained in this document is accurate to the best of our knowledge and representative of the part described

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





20 dB Fixed Attenuator, 7/16 DIN Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz



PE7204-20

TECHNICAL DATA SHEET

Size	
Length, in [mm]	4.9 [124.46]
Width, in [mm]	3.8 [96.52]
Height, in [mm]	2.7 [68.58]
Weight, Ibs [Kg]	3 [1.36]
Connector 1	
Туре	7/16 DIN Female
Contact Material and Plating	Brass, Silver
Body Material and Plating	Brass, Silver
Connector 2	
Туре	7/16 DIN Female
Contact Material and Plating	Brass, Silver
Body Material and Plating	Brass, Silver
Compliance Certifications (visit www.Pasternack.cor	n for current document)
RoHS Compliant	Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level

URL: http://www.pasternack.com/20db-fixed-7-16-female-7-16-female-100-watts-attenuator-pe7204-20-p.aspx

20 dB Fixed Attenuator, 7/16 DIN Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7204-20 CAD Drawing 20 dB Fixed Attenuator, 7/16 DIN Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz

"Y"	4.90		ŀ					
		" _^ " Conne	Type	DIM "A" (REF.)	xx	Input Connector	Output Connector	ctor
	[124.5]		Male	0.68	01	7/16 Female	7/16 Male	
	1	SMA F	SMA Female	0.54	02	N Female	7/16 Male	
					03	7/16 Male	7/16 Female	
		TNC Male	Aale	0.98	04	7/16 Female	7/16 Female	
		TNC F	TNC Female	0.94	05	N Male	7/16 Female	
					90	N Female	7/16 Female	
		N Female	nale	0.95	07	7/16 Female	N Male	
		N Male	e	0.98	08	N Female	N Male	
		- r 			60	SMA Female	N Male	
		7/16 Male	Aale	1.12	10	TNC Female	N Male	
		7/16 F	7/16 Female	1.16	1	7/16 Male	N Female	
		I			12	7/16 Female	N Female	
					13	N Male	N Female	
				1	14	N Female	N Female	
					15	SMA Male	N Female	
					16	SMA Female	N Female	
					17	TNC Male	N Female	
					18	TNC Female	N Female	
, i i i i i i i i i i i i i i i i i i i] –			19	7/16 Female	SMA Male	
	4 60	TINTIO			20	N Female	SMA Male	
•					21	SMA Female	SMA Male	
	[110.0]	CONNECTOR	0K		22	TNC Female	SMA Male	
INPUT					23	7/16 Male	SMA Female	
CONNECTOR	A TOD VIEW				24	7/16 Female	SMA Female	
					25	N Male	SMA Female	
	-				26	N Female	SMA Female	
	2.00				27	SMA Male	SMA Female	
0.4 [10] DP. 🖊	20.5				28	SMA Female	SMA Female	
					29	INC Male	SMA Female	
					30	TNC Female	SMA Female	
					31	7/16 Female	TNC Male	
					32	N Female	TNC Male	
					33	SMA Female	INC Male	
	⊕ ⊕		Ļ		34	INC Female	INC Male	
U.83		Z./O KEF.			35	//16 Male	INC Female	
[21.1]		[68.6]			36	//16 Female	TNC Female	
	()				37	N Male	TNC Female	
		C			30	SMA Malo	TNC Female	
					59	SMA Male	TNC Female	
					40	SMA Female	TNC Female	
					47	TNC Female	TNC Female	
	SIDE VIEW				M-	Indicates Attenuation Level	l Level	
					2			
PAS Pasternack E P.O. Box 16759	P.O. Box 16759 Irvine CA 92623	^{ретис}	NOTE: 1. UNI 3. DIM	S: LESS OTHERWISE { L SPECIFICATIONS I ENSIONS ARE IN IN IENSIONS ARE IN IN	SPECIFIED ARE SUBJ VCHES [mn	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. LL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].	NOMINAL. NT NOTICE AT ANY	TIME.
Phone: (949) 261-192 Website: www.pasternack.com	Phone: (949) 261-1920 Fax: (949) 261-7451 Website: www.pasternack.com E-Mail: sales@pasternack.com	FSCM NO. 53919	0	CAD FILE 091412	12	SCALE N/A	SIZE A	2233