

6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz



TECHNICAL DATA SHEET

PE7206-6

6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz

Pasternack Enterprises line of 100W Attenuators operate from DC to 6 GHz, and are available in 42 different 7/16 DIN, N, SMA and TNC in-series and between-series connector combinations. Our 100W Attenuators are manufactured with Passivated Stainless Steel SMA, TNC and N connectors, and Silver Plated Brass 7/16 DIN connectors. Pasternack 100W Attenuators come in 3 dB, 6 dB, 10 dB, 20 dB, 30 dB, 40 dB, 60 dB values and will operate from -55 to +125 degrees C. Additional connector combinations are available beyond the 42 standard designs, upon request.

- · 100W average power and 2,000W peak power handling capability
- · Operate to 6 GHz
- Temperature range of -55 to +125 degrees C
- · 42 in-series and between series combinations
- 7/16 DIN, SMA, N, TNC Male and Female connectors are available
- · Other connector combinations available upon request

Configuration

Design Fixed, Directional Attenuator
Connector 1 N Female
Connector 2 7/16 DIN Female
Body Material and Plating Aluminum Heatsink, Black Anodized

Electrical Specifications

| Frequency Range, GHz | DC to 6 |
|----------------------------|---------|
| Impedance, Ohms | 50 |
| Attenuation Value, dB | 6 |
| Maximum Input Power, Watts | 100 |
| Maximum VSWR | 1.45:1 |

Frequency 1

| Range, GHz | DC to 2 |
|--------------------------|---------|
| VSWR | 1.2:1 |
| Attenuation Accuracy, dB | ± 0.75 |

Frequency 2

| Range, GHz | 2 to 4 |
|--------------------------|--------|
| VSWR | 1.35:1 |
| Attenuation Accuracy, dB | ± 0.75 |

Frequency 3

| Range, GHz | 4 to 6 |
|--------------------------|--------|
| VSWR | 1.45:1 |
| Attenuation Accuracy, dB | ± 1 |

Mechanical Specifications

Temperature

Operating Range, deg C -55 to +125

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz PE7206-6

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz



TECHNICAL DATA SHEET

PE7206-6

Size

 Length, in [mm]
 4.9 [124.46]

 Width, in [mm]
 3.8 [96.52]

 Height, in [mm]
 2.7 [68.58]

 Weight, lbs [Kg]
 3 [1.36]

Connector 1

Type N Female

Contact Material and Plating Beryllium Copper, Gold Body Material and Plating Stainless Steel, Passivated

Connector 2

Type 7/16 DIN Female
Contact Material and Plating Brass, Silver
Body Material and Plating Brass, Silver

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/6db-fixed-n-female-7-16-female-100-watts-attenuator-pe7206-6-p.aspx

6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7206-6 CAD Drawing

6 dB Fixed Attenuator, N Female To 7/16 DIN Female Directional Rated To 100 Watts Up To 6 GHz

