

10 dB Fixed Attenuator, 7/16 DIN Female To TNC Male Directional Rated To 100 Watts Up To 6 GHz



TECHNICAL DATA SHEET

PE7231-10

Pasternack Enterprises line of 100W Attenuator N, SMA and TNC in-series and between-series Passivated Stainless Steel SMA, TNC and N c 100W Attenuators come in 3 dB, 6 dB, 10 dB,	5
 Other connector combinations available upon 	
Configuration	
Design	Fixed, Directional Attenuator
Connector 1	7/16 DIN Female
Connector 2	TNC Male
Body Material and Plating	Aluminum Heatsink, Black Anodized
Electrical Operifications	
Electrical Specifications	
Frequency Range, GHz	DC to 6
Impedance, Ohms	50
Attenuation Value, dB	10 100
Maximum Input Power, Watts Maximum VSWR	
Maximum VSVVR	1.45:1
Frequency 1	
Range, GHz	DC to 2
VSWR	1.2:1
Attenuation Accuracy, dB	± 0.75
Frequency 2	
Range, GHz	2 to 4
VSWR	1.35:1
Attenuation Accuracy, dB	± 1
Frequency 3	
Range, GHz	4 to 6
VSWR	1.45:1
Attenuation Accuracy, dB	± 1.25
Mechanical Specifications	
Operating Range, deg C	-55 to +125
inventory and certifications: 10 dB Fixed Attenua 6 GHz PE7231-10	SEARCH" on website) to obtain additional part information including price, ator, 7/16 DIN Female To TNC Male Directional Rated To 100 Watts Up To
an information contained in this document is accurat	to the best of our knowledge and representative of the part described

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





10 dB Fixed Attenuator, 7/16 DIN Female To TNC Male Directional Rated To 100 Watts Up To 6 GHz



PE7231-10

TECHNICAL DATA SHEET

Size Length, in [mm] Width, in [mm] Height, in [mm]
Weight, lbs [Kg]
Connector 1 Type Contact Material and Plating Body Material and Plating

Connector 2 Type Contact Material and Plating Coupling Nut Material and Plating Body Material and Plating 4.9 [124.46] 3.8 [96.52] 2.7 [68.58] 3 [1.36]

7/16 DIN Female Brass, Silver Brass, Silver

TNC Male Beryllium Copper, Gold Stainless Steel, Passivated Stainless Steel, Passivated

Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant Yes

Plotted and Other Data

Notes:

Values at 25 °C, sea level

URL: http://www.pasternack.com/10db-fixed-7-16-female-tnc-male-100-watts-attenuator-pe7231-10-p.aspx

10 dB Fixed Attenuator, 7/16 DIN Female To TNC Male Directional Rated To 100 Watts Up To 6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE7231-10 CAD Drawing 10 dB Fixed Attenuator, 7/16 DIN Female To TNC Male Directional Rated To 100 Watts Up To 6 GHz

NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. 2233 Output Connector SMA Female 7/16 Female 7/16 Female 7/16 Female 7/16 Female **TNC Female TNC Female INC Female** INC Female TNC Female INC Female **TNC Female TNC Female** SMA Male SMA Male SMA Male SMA Male 7/16 Male 7/16 Male TNC Male **TNC Male** TNC Male TNC Male N Female Part Number Configuration N Male N Male N Male N Male ∢ SIZE Indicates Attenuation Level Input Connector SCALE N/A SMA Female SMA Female SMA Female SMA Female SMA Female 7/16 Female TNC Female SMA Female 7/16 Female TNC Female TNC Female 7/16 Female INC Female 7/16 Female TNC Female 7/16 Female 7/16 Female TNC Female 7/16 Female 7/16 Female SMA Nale SMA Nale SMA Nale TNC Male 7/16 Male N Female 7/16 Male N Female N Female 7/16 Male N Female N Female 7/16 Male N Female TNC Male N Female N Female TNC Male N Male N Male N Male N Male Š 05 06 07 08 09 10 13 13 15 15 16
 11

 13

 14

 18

 19

 19

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 118

 × 02 33 7 339 340 4 4 2 091412 Connector Type DIM "A" (REF.) 0.68 0.54 1.12 0.98 0.94 0.95 0.98 Table of Information CAD FILE SMA Female **TNC** Female 7/16 Female 2.70 REF. [68.6] SMA Male TNC Male N Female 7/16 Male CONNECTOR N Male 53919 OUTPUT PE72xx-yy . NO FSCM "≺ DWG TITLE 50.8 2.00 E Website: www.pasternack.com | E-Mail: sales@pasternack.com O O Ð Ð 0 O Phone: (949) 261-1920 | Fax: (949) 261-7451 SIDE VIEW TOP VIEW PASTERNACK 124.5 116.8 Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623 4.60 4.90 O O 0 O Ð Ð \bigcirc O CONNECTOR INPUT "∖ 4X M4x0.7 TAP 0.4 [10] DP. 48.3] [21.1] 06 0.83