



7/16 F/M In/Out Bulkhead Coax RF Surge Protector,
698MHz - 2.7GHz, DC Block, 500W, IP67, 40kA,
Filter, Low PIM -155 dBc with Bracket

RF Surge Protectors Technical Data Sheet

PE73SP1007

Features

- Surge current of 40kA
- Max Power 500W
- Frequency range from 698 MHz to 2.7 GHz
- Waterproof IP67 rated
- 7/16 DIN female connector to 7/16 DIN male connector
- DC Block
- Low PIM
- VSWR <1.1:1
- Low insertion loss
- CE & RoHS compliant

Applications

- Cellular communication systems
- Emergency response systems
- Public safety systems
- Industrial

Description

RF surge protector (also known as lightning arrester) PE73SP1007 from Pasternack utilizing a patented spiral inductor design enables an almost instantaneous response to a lightning surge to protect critical hardware while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All Pasternack RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Surge Filter
DC Block

Description	Minimum	Typical	Maximum	Units
Frequency Range	0.698		2.7	GHz
Impedance		50		Ohms
VSWR			1.1:1	
Return Loss			26	dB
Insertion Loss			0.1	dB
Passive Intermodulation			-155	dBc
Input Power, CW 500W @ 920MHz 750W @ 50°C			500	Watts
Surge Current IEC 61000-4-5 8/20µs WAVEFORM			40,000	Amps
Throughput Energy FOR 3kA@ 8/20µs WAVEFORM			0.01	µJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 F/M In/Out Bulkhead Coax RF Surge Protector, 698MHz - 2.7GHz, DC Block, 500W, IP67, 40kA, Filter, Low PIM -155 dBc with Bracket PE73SP1007](#)



7/16 F/M In/Out Bulkhead Coax RF Surge Protector,
698MHz - 2.7GHz, DC Block, 500W, IP67, 40kA,
Filter, Low PIM -155 dBc with Bracket

RF Surge Protectors Technical Data Sheet

PE73SP1007

Mechanical Specifications

Configuration

Input Connector	7/16 DIN Female
Output Connector	7/16 DIN Male

Environmental Specifications

Temperature

Operating Range	-50 to 85 deg C
-----------------	-----------------

Ingress Protection (IP) Rating	IP 67
--------------------------------	-------

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


7/16 F/M In/Out Bulkhead Coax RF Surge Protector, 698MHz - 2.7GHz, DC Block, 500W, IP67, 40kA, Filter, Low PIM -155 dBc with Bracket from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7/16 F/M In/Out Bulkhead Coax RF Surge Protector, 698MHz - 2.7GHz, DC Block, 500W, IP67, 40kA, Filter, Low PIM -155 dBc with Bracket PE73SP1007](#)

URL: <https://www.pasternack.com/7-16-din-surge-protector-2.7ghz-filter-pe73sp1007-p.aspx>

PE73SP1007 CAD Drawing

7/16 F/M In/Out Bulkhead Coax RF Surge Protector, 698MHz - 2.7GHz,
DC Block, 500W, IP67, 40kA, Filter, Low PIM -155 dBc with Bracket



NOTES:
BRACKET AND HARDWARE INCLUDED.
REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

STANDARD	TOLERANCES
.X	±0.2
.XX	±0.01
.XXX	±0.005

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

DWG TITLE

PE73SP1007

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAGE CODE 53919

CAD FILE 3/22/18

SCALE N/A

SIZE A

256