



Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz, DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube

RF Surge Protectors Technical Data Sheet

PE73SP1028

Features

- Surge current of 20kA
- Max Power 375W
- Frequency range from 10 MHz to 1000 MHz
- N Male to N Female connectors
- VSWR 1.1:1
- Multi-strike capability
- CE & RoHS compliant

Applications

- HF, UHF and VHF radios
- Ham radios
- Remote industrial monitoring

Description

RF surge protector (also known as lightning arrester) PE73SP1028 from Pasternack utilizing a proprietary surge protection technology protects critical hardware from lightening events while maintaining the RF performance. This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. Optional weather proofing kit and copper cleaning kit are available for purchase separately. All Pasternack RF surge protector products are available in stock with same day shipping.

Electrical Specifications

Surge Protector Type
DC Handling

Blocking Cap and Gas Tube
DC Block

Description	Minimum	Typical	Maximum	Units
Frequency Range	10		1,000	MHz
Impedance		50		Ohms
VSWR			1.1:1	
Return Loss			26	dB
Insertion Loss			0.1	dB
Input Power, CW			1.5	kWatts
1.5kW @ 10MHz TO 50MHz				
375W @ 125MHz TO 220MHz				
125W @ 220MHz TO 700MHz				
50W @ 700MHz TO 1000MHz				
Surge Current			20	kA
IEC 61000-4-5 8/20µs WAVEFORM				
Turn On Voltage		600 ±20%		Volts
Throughput Energy			3.5	mJ
@ 3kA 8/20µs WAVEFORM				

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz, DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube PE73SP1028](#)



Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz, DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube

RF Surge Protectors Technical Data Sheet

PE73SP1028

Mechanical Specifications

Configuration

Input Connector

N Male

Output Connector

N Female

Environmental Specifications

Temperature

Operating Range

-50 to +50 deg C

Storage Range

-55 to +85 deg C

Ingress Protection (IP) Rating

None

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz, DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz, DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube PE73SP1028](#)

URL: <https://www.pasternack.com/type-n-surge-protector-1ghz-blocking-cap-gas-tube-pe73sp1028-p.aspx>

PE73SP1028 CAD Drawing

Type N M/F In/Out Bulkhead Coax RF Surge Protector, 10MHz - 1GHz,
DC Block, 1.5kW, None, 3.5mJ, 20kA, Blocking Cap and Gas Tube



NOTES:

HARDWARE INCLUDED.

REGULATORY COMPLIANCE:

CE2011/65/EU (RoHS DIRECTIVE)

STANDARD TOLERANCES

.X ±0.2
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY
ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE73SP1028

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAGE CODE 53919

CAD FILE 3/23/18

SCALE N/A

SIZE A

256