

SMA PIN-Schottky Limiter, 100 Watts Peak Power, 14 dBm Flat Leakage, 11 GHz to 18 GHz

# **Limiters Technical Data Sheet**

## **Electrical Specifications**

Internal DC Block

Description	Minimum	Typical	Maximum	Units
Frequency Range	11		18	GHz
Insertion Loss		2.4		dB
Input VSWR		2.2:1		
Output VSWR		2.2:1		
Leakage (CW) @ 1 Watt CW			+14	dBm
Leakage (Peak)			+19	dBm
Recovery Time		200		μs
Input Power (CW)			1	Watt
Input Power (Peak) @1us pulse, 0.1% Duty	Cycle		100	Watt
Derated to 20% @ +125°C				
Limiting Threshold		+4		dBm

#### **Electrical Specification Notes:**

Values at 25°C, sea level. Specification @ +25°C and -10 dBm input power.

#### **Mechanical Specifications**

Size Length Width Height Weight Body Material and Plating

#### **Configuration** Style

Package Style Impedance Connector 1 Connector 2

### **Environmental Specifications**

**Temperature** Operating Range Storage Range 1.27 in [32.26 mm] 0.31 in [7.87 mm] 0.31 in [7.87 mm]

0.2 lbs [90.72 g] Passivated Stainless Steel


PIN-Schottky Limiter Connectorized Module 50 Ohms SMA Male SMA Female

-55 to +90 deg C -65 to +125 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA PIN-Schottky Limiter, 100 Watts Peak Power, 14 dBm Flat Leakage, 11 GHz to 18 GHz PE8038

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com









SMA PIN-Schottky Limiter, 100 Watts Peak Power, 14 dBm Flat Leakage, 11 GHz to 18 GHz



# Limiters Technical Data Sheet

**PE8038** 

Shock Vibration 50 G's, 11 msec 20G, 100 to 2000Hz

Compliance Certifications (visit www.Pasternack.com for current document) Not RoHS Compliant

REACH Compliant

06/18/2012

## **Plotted and Other Data**

Notes:

• Values at 25°C, sea level.

SMA PIN-Schottky Limiter, 100 Watts Peak Power, 14 dBm Flat Leakage, 11 GHz to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA PIN-Schottky Limiter, 100 Watts Peak Power, 14 dBm Flat Leakage, 11 GHz to 18 GHz PE8038

URL: http://www.pasternack.com/50-ohm-sma-pin-schottky-limiter-12-dbm-1000-mhz-18000-mhz-pe8038-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



PE8038 CAD Drawing SMA PIN-Schottky Limiter, 100 Watts Peak Power,

14 dBm Flat Leakage, 11 GHz to 18 GHz

