

Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female



PE8300

Isolators Technical Data Sheet

Features

- 1 to 2 GHz Frequency Range
- Max Forward and Reverse Power 10 Watts CW
- Insertion Loss < 0.6 dB

Applications

- Radar Systems
- Telecom Infrastructure
- Microwave Radio Systems

- MilitaryWireless Radio Systems
- Communication Systems
- R&D Labs

Description

The PE8300 is a single junction isolator offering a forward and reverse power rating of 10 Watts CW over an operational frequency band of 1 to 2 GHz. This coaxial isolator uses SMA female connectors on all ports and has a minimum of 18 dB isolation.

VSWR < 1.35:1

Isolation > 18 dB

SMA Female Connectors

Pasternack offers a wide variety of isolators to fit your needs. These are two-port devices that transmit microwave or radio frequency power in one direction only and block the signal in the opposite direction. They can be thought of as a diode for RF energy. Isolators are used to isolate equipment from the effects of conditions outside of the equipment. For instance they are used to prevent a microwave source being detuned by a mismatched load. Pasternack's isolators feature excellent insertion loss, high isolation and reliability.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	1		2	GHz
Impedance		50		Ohms
Insertion Loss			0.6	dB
Isolation	18			dB
VSWR			1.35:1	
Forward Power, CW			10	Watts
Reverse Power, CW			10	Watts
				Traile

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size	
Length	2.6 in [66.04 mm]
Width	2.6 in [66.04 mm]
Height	0.75 in [19.05 mm]
Weight	0.59 lbs [267.62 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female PE8300

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451



Sales@Pasternack.com • Techsupport@Pasternack.com

.



Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female



PE8300

Isolators Technical Data Sheet

Configuration Design Direction Package Style Connector 1 Connector 2

Single Junction 1 to 2 Connectorized SMA Female SMA Female

Environmental Specifications

Temperature **Operating Range**

+10 to +40 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data Notes:

Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female PE8300

URL: https://www.pasternack.com/50-ohm-sma-isolator-1000-mhz-2000-mhz-20-watts-18-db-pe8300-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Sales@Pasternack.com • Techsupport@Pasternack.com





PE8300 CAD Drawing

Isolator With 18 dB Isolation From 1 GHz to 2 GHz, 10 Watts And SMA Female

