



2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees,
TTL Control, 75nsec Speed, SMA

TECHNICAL DATA SHEET

PE86GM2002

The PE86GM2002 is a 0° to 180° Bi-Phase Modulator that operates across a frequency range from 2000 MHz to 4000 MHz. This modulator takes a TTL level digital bits stream and encodes it onto the RF carrier using 2 Phase Shift Keying (2PSK). 2 Phase Shift Keying utilizes 2 phases which are separated by 180°. Impressive typical performance includes low insertion loss of 2.5 dB, < 75 switching speed, 20 dB carrier suppression, and 0.5W CW maximum RF input power. The design is bidirectional with input and output RF ports, and employs dual bias voltages (+5/-5 Vdc) and integrated TTL processing to phase modulate the control data onto the RF, and operates across a wide temperature range of -55°C to +85°C. The rugged and compact package uses TTL, Bias, Ground pins, and field replaceable SMA Female connectors. The high reliability design meets MIL-STD-202 environmental test conditions for Humidity, Shock, Vibration, Altitude, and Temperature Cycle.

Features

- 0° to 180° Bi-Phase Modulator module
- 2 Phase Shift Keying (2PSK) Modulation
- Frequency Range: 2000 MHz to 4000 MHz
- Insertion Loss: 2.5 dB typ
- Switching Speed: < 75 ns typ
- Carrier Suppression: 20 dB
- Compact Package Design
- SMA Connectors
- Dual Bias Voltage: +5/-5 Vdc
- Integrated TTL Driver
- -40°C to +85°C Operating Temperature
- Designed to meet MIL-STD-202 Test Conditions
- Bi-Directional Operation

Applications

- Communication Systems
- Microwave Radio
- Radar
- High Data Rate Test & Measurement
- Serial Data Transmission
- Basestation Infrastructure

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		4	GHz
RF Input Power (CW)			+20	dBm
Maximum Peak RF (Survival) 1μs Pulse Width			0.5	Watts
Impedance		50		Ohms
VSWR		1.5:1	2:1	
Insertion Loss		2.5	3	dB
Carrier Suppression		20		dB
Switching Speed		75		ns
Phase State (Off)		0		degrees
Phase State (On)		180		degrees
Bias Voltage (+)		5		Volts
Bias Voltage (-)		-5		Volts
Bias Current @ +5 VDC		35	75	mA
Bias Current @ -5 VDC		5	20	mA

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA PE86GM2002](#)



2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees,
TTL Control, 75nsec Speed, SMA

TECHNICAL DATA SHEET

PE86GM2002

Mechanical Specifications

Size

Length	1 in	[25.4mm]
Width	1 in	[25.4 mm]
Height	0.5 in	[12.7 mm]
Weight	0.125 lbs	[56.7 g]

Configuration

Design	Bi-Phase Modulator
Connector Option	Field Replaceable
RF Connector	SMA Female

Environmental Specifications

Temperature

Operating Range	-55°C to +85°C
Storage Range	-65°C to +125°C

Humidity	MIL-STD-202F, Method 103B Cond. B
Shock	MIL-STD-202F, Method 213B Cond. B
Vibration	MIL-STD-202F, Method 204D Cond. B
Altitude	MIL-STD-202F, Method 105C Cond. B
Temperature Cycle	MIL-STD-202F, Method 107D Cond. A

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA PE86GM2002](#)




2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees,
TTL Control, 75nsec Speed, SMA


TECHNICAL DATA SHEET

PE86GM2002

Functional Block Diagram



Typical Performance Data




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA PE86GM2002](#)



2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees,
TTL Control, 75nsec Speed, SMA

TECHNICAL DATA SHEET

PE86GM2002



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA PE86GM2002](#)



2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees,
TTL Control, 75nsec Speed, SMA

TECHNICAL DATA SHEET

PE86GM2002

2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA PE86GM2002](https://www.pasternack.com/pe86gm2002-p.aspx)

URL: <https://www.pasternack.com/pe86gm2002-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE86GM2002 CAD Drawing

2 GHz to 4 GHz, Bi-Phase Modulator, 0/180 Degrees, TTL Control, 75nsec Speed, SMA

