

## SMC Plug to BNC Male Adapter



## RF Adapters Technical Data Sheet

PE9139

### Configuration

- SMC Plug Connector 1
- BNC Male Connector 2

- 50 Ohms
- Straight Body Geometry

#### **Features**

- SMC Interface compliant with MIL-STD-348A
- BNC Interface compliant with MIL-STD-348A
- Gold Plated Brass Contact
- 30 µ-in min Gold Contact Plating

### **Applications**

Allows Connection Between Series

General Purpose Test

#### Description

Pasternack's PE9139 SMC plug to BNC male adapter is part of our full line of RF components available for same-day shipping. Our SMC to BNC adapter has a plug to male gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

#### **Mechanical Specifications**

Size

 Length
 1.22 in [30.99 mm]

 Width
 0.57 in [14.48 mm]

 Weight
 0.034 lbs [15.42 g]

Description	Connector 1	Connector 2
Туре	SMC Plug	BNC Male
Polarity	Standard	Standard
Interface Specification	MIL-STD-348A	MIL-STD-348A
Hex Size	1/4 in.	
Mating Torque	3 to 5 in-lbs [0.34 to 0.57 Nm]	

### **Material Specifications**

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMC Plug		BNC Male	
Contact	Brass	Gold	Brass	Gold

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Plug to BNC Male Adapter PE9139

ISO 9001 : 2008 Registered





## SMC Plug to BNC Male Adapter



## RF Adapters Technical Data Sheet

PE9139

		30 μ-in minimum		30 μ-in minimum
Insulation	PTFE		PTFE	
Body	Brass	Nickel	Brass	Nickel
		100 μ-in minimum		100 μ-in minimum
Coupling Nut Bra	Brass	Nickel	Brass	Nickel
		100 μ-in minimum		100 μ-in minimum

#### Compliance Certifications (see product page for current document)

SMC Plug to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Plug to BNC Male Adapter PE9139

URL: https://www.pasternack.com/smc-plug-bnc-male-straight-adapter-pe9139-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



# PE9139 CAD Drawing

SMC Plug to BNC Male Adapter

