



TECHNICAL DATA SHEET

PE9283

**SMC Jack to SMB Jack Adapter**

**Configuration**

|                |          |
|----------------|----------|
| Connector 1    | SMC Jack |
| Impedance 1    | 50 Ohms  |
| Connector 2    | SMB Jack |
| Impedance 2    | 50 Ohms  |
| Adapter Design | Standard |
| Body Style     | Straight |

**Mechanical Specifications**

**Temperature**

|                        |             |
|------------------------|-------------|
| Operating Range, deg C | -65 to +165 |
|------------------------|-------------|

**Size**

|                     |               |
|---------------------|---------------|
| Length, in [mm]     | 0.686 [17.42] |
| Width/Dia., in [mm] | 0.25 [6.35]   |

**Connector 1**

|                                       |               |
|---------------------------------------|---------------|
| Type                                  | SMC Jack      |
| Inner Conductor Material and Plating  | Gold          |
| Inner Conductor Plating Specification | MIL-G-45204   |
| Body Material and Plating             | Brass, Nickel |
| Dielectric Type                       | Teflon        |

**Connector 2**

|                                       |               |
|---------------------------------------|---------------|
| Type                                  | SMB Jack      |
| Inner Conductor Material and Plating  | Gold          |
| Inner Conductor Plating Specification | MIL-G-45204   |
| Body Material and Plating             | Brass, Nickel |
| Dielectric Type                       | Teflon        |

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

|                |     |
|----------------|-----|
| RoHS Compliant | Yes |
|----------------|-----|

**Plotted and Other Data**

|        |                            |
|--------|----------------------------|
| Notes: | Values at 25 °C, sea level |
|--------|----------------------------|


URL: <http://www.pasternack.com/smc-jack-smb-jack-straight-adapter-pe9283-p.aspx>

SMC Jack to SMB Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



**PE9283 CAD Drawing**  
SMC Jack to SMB Jack Adapter



DWG TITLE

**PE9283**

NOTES:  
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
 3. DIMENSIONS ARE IN INCHES [mm].

REV. -

FSCM NO. 53919

CAD FILE 090402

SCALE N/A

SIZE A

127



**PASTERNAK®**  
 Pasternack Enterprises, Inc.  
 P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)