

SSMA Female to N Female Adapter



PE9354

TECHNICAL DATA SHEET

SSMA Female to N Female Adapter	
Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style	SSMA Female 50 Ohms N Female 50 Ohms Standard Straight
Mechanical Specifications Temperature Operating Range,deg C	-65 to +165
Size Length, in [mm] Width/Dia., in [mm]	1.225 [31.12] 0.7 [17.78]
Connector 1 Type Inner Conductor Material and Plating Inner Conductor Plating Specification Body Material and Plating Dielectric Type	SSMA Female Gold MIL-G-45204 Brass, Nickel Teflon
Connector 2 Type Inner Conductor Material and Plating Inner Conductor Plating Specification Body Material and Plating Dielectric Type	N Female Gold MIL-G-45204 Brass, Nickel Teflon
Compliance Certifications (visit www.Pasternack. RoHS Compliant	com for current document) Yes
Plotted and Other Data Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/ssma-female-n-fe	emale-straight-adapter-pe9354-p.aspx

SSMA Female to N Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



industry.

1

PE9354 CAD Drawing

SSMA Female to N Female Adapter

