



## 75 Ohm BNC Male to BNC Male Adapter

### RF Adapters Technical Data Sheet

PE9364

#### Configuration

- BNC Male Connector 1
- BNC Male Connector 2
- 75 Ohms
- Straight Body Geometry

#### Features

- Max VSWR of 1.5:1 up to 300 MHz
- Gold Plated Brass Contact

#### Applications

- General Purpose Test

#### Description

Pasternack's PE9364 75 ohm BNC male to BNC male adapter is part of our full line of RF components available for same-day shipping. Our BNC to BNC adapter has a male to male gender configuration. PE9364 BNC male to BNC male adapter operates to 300 MHz. The Pasternack RF adapter provides good VSWR of 1.5:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	MHz
VSWR			1.5:1	
Operating Voltage (AC)			500	Vrms

#### Mechanical Specifications

<b>Size</b>	
Length	1.244 in [31.6 mm]
Width	0.571 in [14.5 mm]
Weight	0.048 lbs [21.77 g]

Description	Connector 1	Connector 2
Type	BNC Male	BNC Male
Polarity	Standard	Standard

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm BNC Male to BNC Male Adapter PE9364](#)



## 75 Ohm BNC Male to BNC Male Adapter

### RF Adapters Technical Data Sheet

PE9364

#### Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	BNC Male		BNC Male	
Contact	Brass	Gold	Brass	Gold
Insulation	PTFE		PTFE	
Body	Brass	Nickel 100 µ-in minimum	Brass	Nickel 100 µ-in minimum
Gasket	Silicone		Silicone	
Coupling Nut	Brass	Nickel 100 µ-in minimum	Brass	Nickel 100 µ-in minimum

#### Environmental Specifications

##### Temperature

Operating Range

-65 to +165 deg C

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:


75 Ohm BNC Male to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm BNC Male to BNC Male Adapter PE9364](#)

URL: <https://www.pasternack.com/bnc-male-bnc-male-straight-adapter-pe9364-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9364 CAD Drawing  
75 Ohm BNC Male to BNC Male Adapter



LABEL  
"PASTERNAK"  
PE9364"

STANDARD TOLERANCES

.X ±0.2  
.XX ±0.1  
.XXX ±0.05

\*STANDARD TOLERANCES APPLY  
ONLY TO DIMENSIONS IN INCHES



Pasternack Enterprises, Inc.  
P.O. Box 16759 | Irvine | CA | 92623  
Phone: (949) 261-1920 | Fax: (949) 261-7451  
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE9364

FSCM NO. 53919

CAD FILE 061016

SCALE N/A

SIZE A

2233

NOTES:  
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
3. DIMENSIONS ARE IN INCHES [mm].