

SSMB Plug to BNC Male Adapter



**PE9393** 

## **TECHNICAL DATA SHEET**

SSMB Plug to BNC Male Adapter	
Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style	SSMB Plug 50 Ohms BNC Male 50 Ohms Standard Straight
Mechanical Specifications Temperature Operating Range,deg C	-65 to +165
<b>Size</b> Length, in [mm] Width/Dia., in [mm]	1.2 [30.48] 0.57 [14.48]
<b>Connector 1</b> Type Inner Conductor Material and Plating Inner Conductor Plating Specification Body Material and Plating Dielectric Type	SSMB Plug Gold MIL-G-45204 Brass, Nickel Teflon
<b>Connector 2</b> Type Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Body Material and Plating Dielectric Type	BNC Male Gold MIL-G-45204 Brass, Nickel Brass, Nickel Teflon
Compliance Certifications (visit www.Pasternack.com fo RoHS Compliant	r current document) Yes
Plotted and Other Data Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/ssmb-plug-bnc-male-st	raight-adapter-pe9393-p.aspx
SSMB Plug to BNC Male Adapter from Pasternack Enterp	rises has same day shipment fo

SSMB Plug to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

## ISO 9001 : 2008 Registered



## PE9393 CAD Drawing

SSMB Plug to BNC Male Adapter

