

### 2.4mm Male to 2.4mm Female Adapter



# **RF Adapters Technical Data Sheet**

PE9452

### Configuration

- 2.4mm Male Connector 1
- 2.4mm Female Connector 2

- 50 Ohms
- Straight Body Geometry

#### **Features**

Max VSWR of 1.3:1 up to 50 GHz

• Gold Plated Beryllium Copper Contact

### **Applications**

Connector Saver

General Purpose Test

#### Description

Pasternack's PE9452 2.4mm male to 2.4mm female adapter is part of our full line of RF components available for same-day shipping. The 2.4mm connector mates mechanically with commercially available 1.85mm (V) connectors. Our 2.4mm to 2.4mm adapter has a male to female gender configuration. PE9452 2.4mm male to 2.4mm female adapter operates to 50 GHz. The Pasternack RF adapter provides good VSWR of 1.3:1 maximum. The PE9452 Pasternack RF adapter can also be used as a connector saver to extend equipment life.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

#### **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		50	GHz
VSWR			1.3:1	

#### Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 18	18 to 26.5	26.5 to 50			GHz
VSWR, Max	1.1:1	1.2:1	1.3:1			

Electrical Specification Notes: Values at 25° sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Male to 2.4mm Female Adapter PE9452

ISO 9001 : 2008 Registered



# 2.4mm Male to 2.4mm Female Adapter



# **RF Adapters Technical Data Sheet**

PE9452

#### **Mechanical Specifications**

Size

 Length
 0.793 in [20.14 mm]

 Width
 0.312 in [7.92 mm]

 Weight
 0.017 lbs [7.71 g]

Description	Connector 1	Connector 2
Туре	2.4mm Male	2.4mm Female
Polarity	Standard	Standard
Hex Size	5/16 inch	

#### **Material Specifications**

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	2.4mm Male		2.4mm Female		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
Outer Conductor Pa	assivated Stainless Steel		Passivated Stainless Steel		

### **Environmental Specifications**

Temperature

Operating Range -65 to +125 deg C

Compliance Certifications (see product page for current document)

**Plotted and Other Data** 

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Male to 2.4mm Female Adapter PE9452





# 2.4mm Male to 2.4mm Female Adapter



# **RF Adapters Technical Data Sheet**

**PE9452** 

2.4mm Male to 2.4mm Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Male to 2.4mm Female Adapter PE9452

URL: https://www.pasternack.com/2.4mm-male-2.4mm-female-straight-adapter-pe9452-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451





PF9452 RFV 1.1

# PE9452 CAD Drawing

2.4mm Male to 2.4mm Female Adapter

