

Precision N Female to BNC Female Adapter



RF Adapters Technical Data Sheet

PE9492

Configuration

- N Female Connector 1
- BNC Female Connector 2
- •50 Ohms

- Precision Design
- Straight Body Geometry

Features

- Max VSWR of 1.2:1 up to 8 GHz
- N Interface compliant with MIL-STD-348
- BNC Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact

Applications

- Allows Connection Between Series
- General Purpose Test
- Precision Test & Measurement

Description

Pasternack's PE9492 precision type N female to BNC female adapter is part of our full line of RF components available for same-day shipping. Our type N to BNC adapter has a female to female gender configuration in a precision design. PE9492 type N female to BNC female adapter operates to 8 GHz. The Pasternack RF adapter provides excellent VSWR of 1.2:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		8	GHz
VSWR		1.2:1		

Mechanical Specifications

Size

 Length
 1.852 in [47.04 mm]

 Width
 0.625 in [15.88 mm]

 Weight
 0.099 lbs [44.91 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision N Female to BNC Female Adapter PE9492

ISO 9001 : 2008 Registered



Precision N Female to BNC Female Adapter



RF Adapters Technical Data Sheet

PE9492

Connector 1	Connector 2
N Female	BNC Female
Standard	Standard
MIL-STD-348	MIL-STD-348
	N Female Standard

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	N Female		BNC Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Outer Conductor Pa	assivated Stainless Steel		Brass	Nickel

Environmental Specifications

Temperature

-65 to +125 deg C **Operating Range**

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Precision N Female to BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision N Female to BNC Female Adapter PE9492

URL: https://www.pasternack.com/n-female-bnc-female-straight-adapter-pe9492-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE9492 CAD Drawing

Precision N Female to BNC Female Adapter

