

75 Ohm N Female to SMB Jack Adapter



RF Adapters Technical Data Sheet

PE9583

Configuration

- N Female Connector 1
- SMB Jack Connector 2

Features

- N Interface compliant with MIL-STD-348
- SMB Interface compliant with MIL-STD-348

Applications

Allows Connection Between Series
General Purpose Test

Description

Pasternack's PE9583 75 ohm type N female to SMB jack adapter is part of our full line of RF components available for sameday shipping. Our type N to SMB adapter has a female to jack gender configuration.

•75 Ohms

Straight Body Geometry

Contact Plating per MIL-G-45204

Gold Plated Contact

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/ disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size Length Width Weight	0.625 in [1	1.383 in [35.13 mm] 0.625 in [15.88 mm] 0.064 lbs [29.03 g]	
Description	Connector 1	Connector 2	
Туре	N Female	SMB Jack	

Туре	N Female	SMB Jack	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348	MIL-STD-348	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Female to SMB Jack Adapter PE9583

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





75 Ohm N Female to SMB Jack Adapter

RF Adapters Technical Data Sheet

PE9583

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	N Female		SMB Jack		
Contact		Gold		Gold	
		MIL-G-45204		MIL-G-45204	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Nickel	Brass	Nickel	
		QQ-N-290		QQ-N-290	

Environmental Specifications

Temperature Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm N Female to SMB Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Female to SMB Jack Adapter PE9583

URL: https://www.pasternack.com/n-female-smb-jack-straight-adapter-pe9583-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451



PE9583 REV 1.1



PE9583 CAD Drawing 75 Ohm N Female to SMB Jack Adapter

