

FME Plug to FME Plug Adapter



TECHNICAL DATA SHEET

PE9696

FME Plug to FME Plug Adapter

Configuration

Connector 1FME PlugImpedance 150 OhmsConnector 2FME PlugImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 0.995 [25.27] Width/Dia., in [mm] 0.391 [9.93]

Connector 1

Type FME Plug
Inner Conductor Material and Plating Brass, Gold
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Connector 2

Type FME Plug Inner Conductor Material and Plating Brass, Gold Body Material and Plating Brass, Nickel Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/fme-plug-fme-plug-straight-adapter-pe9696-p.aspx

FME Plug to FME Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



FME Plug to FME Plug Adapter

