





Gain Horns with Waveguide to Coax Adapters Tech-

PE9859/NF-20

Configuration

Design WR-137 Standard Gain Horn

Pattern Directional Polarization Linear Coaxial Interface N Female

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	5.85		8.2	GHz
Impedance		50		Ohms
Waveguide Standard Gain Horn				
Gain		20		dB
Horizontal Half Power Beam Width		18.8		Degrees
Vertical Half Power Beam Width		18.7		Degrees
Waveguide to Coaxial Adapter				
Input VSWR			1.25:1	

Mechanical Specifications

Size

Weight 1.5 lbs [680.39 g]

RF Connector

Type N Female

Waveguide Interface

Waveguide Size WR-137

Environmental Specifications

Compliance Certifications (see product page for current document)

Plotted and Other Data

2 Dimensional OML Drawing PE9859/NF-20 Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-137 Waveguide Standard Gain Horn Antenna Operating From 5.85 GHz to 8.2 GHz With a Nominal 20 dB Gain N Female Input PE9859/NF-20





WR-137 Waveguide Standard Gain Horn Antenna Operating From 5.85 GHz to 8.2 GHz With a Nominal 20 dB Gain N Female Input



Gain Horns with Waveguide to Coax Adapters Tech-

PE9859/NF-20

WR-137 Waveguide Standard Gain Horn Antenna Operating From 5.85 GHz to 8.2 GHz With a Nominal 20 dB Gain N Female Input from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-137 Waveguide Standard Gain Horn Antenna Operating From 5.85 GHz to 8.2 GHz With a Nominal 20 dB Gain N Female Input PE9859/NF-20

URL: https://www.pasternack.com/standard-gain-horn-waveguide-size-wr137-20-db-gain-n-female-pe9859nf-20-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE9859/NF-20 CAD Drawing
WR-137 Waveguide Standard Gain Horn Antenna Operating From 5.85 GHz to 8.2 GHz With a Nominal 20 dB Gain N Female Input

