

# WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input



## Gain Horns with Waveguide to Coax Adapters Tech-

PE9863/SF-20

Configuration

Design WR-284 Standard Gain Horn

Pattern Directional Polarization Linear Coaxial Interface **SMA Female** 

**Electrical Specifications** 

Minimum	Typical	Maximum	Units
2.6		3.95	GHz
	50		Ohms
	20		dB
	16.5		Degrees
	17.2		Degrees
		1.25:1	
		2.6 50 20 16.5	2.6 3.95 50  20  16.5  17.2

#### **Mechanical Specifications**

Size

Weight 20 lbs [9.07 Kg]

**RF Connector** 

SMA Female Type

**Waveguide Interface** 

Waveguide Size WR-284

#### **Environmental Specifications**

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

2 Dimensional OML Drawing Notes:

PE9863/SF-20

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input PE9863/SF-20





# WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input



## Gain Horns with Waveguide to Coax Adapters Tech-

PE9863/SF-20

WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input PE9863/SF-20

URL: https://www.pasternack.com/standard-gain-horn-waveguide-size-wr284-20-db-gain-sma-female-pe9863sf-20-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



**PE9863/SF-20 CAD Drawing**WR-284 Waveguide Standard Gain Horn Antenna Operating From 2.6 GHz to 3.95 GHz With a Nominal 20 dB Gain SMA Female Input

